

Classic Construction:

Classic casebody is constructed using fully doweled 0.75" particle board with double sided thermal fused laminate (TFL) with a 0.75" sub-bottom with matching 3mm PVC edge banding. Integrated, 1" caster base, matching 3mm PVC edge banding. 20A GFI protected AC duplex electrical outlet (back of unit). Casebody is 48.25"W x 28"D

The top has a choice of a 1.25" black chemical resistant high pressure laminate (HPL) with a phenolic backer and matching 3mm PVC edge banding or a 1" phenolic resin and cellulose fiber composite top over a 0.75" sub-top. Top is 31"D x 53"L (77" wing span w/optional hinged wings).

Drawers are fully doweled, 0.5" white TFL box w/.5mm PVC edgebanding, 0.75" matching TFL front w/3mm PVC edge banding, wire pulls, optional integrated locks and full extension side mount steel ball bearing glides.

Doors are 0.75" double sided TFL, 3mm PVC edge banding, wire pulls, 6-point adjustable concealed hinges and optional integrated locks.

Shelves are double-sided TFL, adjustable shelves have four double-pin shelf clips per shelf to prevent the shelves from sliding out or tipping. Fixed shelves are fully doweled.


Each unit has 3" heavy-duty casters (two locking, two non-locking and requires field assembly).

Demonstration mirror/whiteboard is 27.75"W x 1"D x 22.5"H and easily mounts on .5" diameter crossbars and held secure with nylon screws on mounting brackets. Shatter resistant acrylic mirror and marker board combo. Solid oak frame.

Shipping Class: Density Based

NMFC#: 80440

Assembly: Some assembly required



Fully doweled .75" double-sided TFL casebody




Fully doweled 0.5" white TFL drawer box and 0.75" sub-front



3mm PVC edgebanding on casebody, drawer fronts and doors



4" Wire Pull



Integrated locks (optional)




Full extension side mount steel ball bearing glides



20A GFI protected AC duplex electrical outlet (back of unit) (EO)



3" heavy duty casters



6-point adj. hinge



Stainless Steel sink kit with vacuum supply (SK) (optional)



12" L hinged wings feature quick lock arm supports (HW) (wings are optional)



Poly holding containers fit neatly under sink adjacent to 2 adjustable shelves (optional)



Demonstration mirror/whiteboard, uprights and crossbar (DM) (optional)

Premium REplay® cabinets are constructed the same as the Classic **EXCEPT** the Premium cabinet components are **double sided high pressure laminate (HPL)** in place of the double sided TFL. Please NOTE that drawer boxes will always have white thermal fused laminate (TFL).

Example of Classic and Premium Model #'s:

Classic: SC6340-AC-09/C

Premium: SC6340-AC-09/P



SC8340-AC

*Shown with optional hinged wings

Science Workstation

Case body: 48.25"W x 28"D

Top*: 31"D x 53"L (77" wing span)

<i>Model #</i>	<i>Wgt</i>	<i>Description</i>	<i>Overall Hgt."</i>
SC6340-AC-09C	275	Black Chemical Resistant Laminate Top, 2 Sliding Doors, GFI Electrical Outlet	36
SC8340-AC	303	Black Phenolic Top, 2 Sliding Doors, GFI Electrical Outlet	36

*With optional extension wings down. Add 12" for each wing that is up.



SC8316-AC

Instructor Desk

Case body: 48.25"W x 28"D

Top*: 31"D x 53"L (77" wing span)

<i>Model #</i>	<i>Wgt</i>	<i>Description</i>	<i>Overall Hgt."</i>
SC6316-AC-09C	452	Black Chemical Resistant Laminate Top, Double Doors Left Side, 3 Drawers Right Side, GFI Electrical Outlet	36
SC8316-AC	480	Black Phenolic Top, Double Doors Left Side, 3 Drawers Right Side, GFI Electrical Outlet	36

*With extension wings down. Add 12" for each wing that is up.